

Inquiry form



**Specifications:**

*Diametre round cartridge heater:*  mm       *unipolar (standard 24V)*  
 *Cross section square cartridge heater:*  mm  
*Total length:*  mm      *Voltage:*  V  
*Quantity:*  pieces      *Wattage:*  W

**Options:**

Thermocouple (p. 8)

*Thermosensor type J (Fe-CuNi, red / blue)*       *Thermosensor type K (NiCr-Ni, red / green)*

Connection Type (p. 9)

*Type I internally connected (standard for  $\varnothing \leq 8\text{mm}$ )*  
 *Type N externally connected (standard for  $\varnothing > 8\text{mm}$ )*  
 *Type F contacted in ceramic cap*

Leads Type (p. 9)

*Fibre glass insulated leads (standard 250mm) 300°C*       *PTFE insulated leads (no standard) 260°C*  
 *Silicone insulated leads (no standard) 180°C*       *High temperature leads (no standard) 500°C*

*Leads length:*  mm

*Earth lead:*  Yes       No

Protection Sleeve (p. 14)

*Silicon impregnated fibreglass sleeve*       *Braided metal sleeve*  
 *Stainless steel sleeve*       *Flexible metal conduit*  
 *Silicone cable*

*Length:*  mm

Termination Type (p. 10)

*Type A*       *Type B*       *Type C*       *Type D*

*Miscellaneous*

**Sender address:**

*Company:*       *Name:*   
*Street:*       *Telephone:*   
*Zip / Town:*  /       *E-Mail:*

Telephone: +49 - (0)23 73 - 95 90-0  
 Telefax: +49 - (0)23 73 - 95 90-30

